

BPS101 Tungsten Halogen Light Source



The BPS101 is a low-cost high-performance constant current light source which uses a replaceable tungsten halogen bulb rated for 10,000 hours. This device uses a constant current setting which provides precision current control allowing for stable performance.

A remote control port is provided on the rear for versatile remote On / Off modulation, operating current monitoring, and external operating current control. Slow ramp start is built into the source to ensure stability and long-life operation. The BPS101 features an SMA 905 connector for fiber coupling. No fiber alignment is necessary and is ideal for visible and near IR spectroscopic applications.


Highlights:

- Spectral Range 350 to > 2600nm
- Compact and Light Weight
- Constant Current
- 10,000 Hour Rating
- 2800 K Color Temperature

Applications:

- Transmission Spectroscopy
- Absorption Spectroscopy
- Reflectance Spectroscopy
- Much more...


Typical Relative Spectral Intensity:



Specifications:

Light Source	Tungsten Halogen Lamp
Spectral Output Range	350 to > 2600nm
Color Temperature	2800 K
Lamp Ratings	6 V DC @ < 1.1 A
Rated Life	10,000 hours
Light Coupling	SMA 905
Modulation Port	4 Pin RJ11 Connector
Control Functions	Modulation, On / Off, Current Monitoring
Modulation Input	DC 0-5 V to Set Output Power
Digital Modulation	TTL Logic Input, 'Low' or 'High' up to 100 Hz
Current Monitoring	DC Output 0 - 1 V corresponding with 0-1A lamp current
Max Dimensions	4.0in x 2.5in x 1.6in (L x W x H)
Weight	0.5 lbs
Operating Temperature	0° to 40°C
Relative Humidity	0-85% RH non condensing
AC Adapter Input	100-240 V AC (50 - 60 Hz)
Power Supply Output	6 V DC +/- 2.5% @ 2.0 A
Output Current Stability	+/- 0.1%

Transmission / Absorption Experiment Setup



Dimensions (inches):

